

### KEY FEATURES

- High power handling: 800 W program power
- 3" copper wire voice coil
- High sensitivity: 99 dB (1W / 1m)
- FEA optimized ceramic magnetic circuit
- Weatherproof cone treatment for both sides of the cone
- Extended controlled displacement:  $X_{\max} \pm 6,3$  mm
- 30 mm peak-to-peak excursion before damage
- Low harmonic distortion and linear response
- Wide range of applications of low and mid-low frequencies



### TECHNICAL SPECIFICATIONS

Nominal diameter	380 mm	15 in
Rated impedance		8 $\Omega$
Minimum impedance		6,4 $\Omega$
Power capacity <sup>1</sup>		400 W <sub>AES</sub>
Program power <sup>2</sup>		800 W
Sensitivity	99 dB	1W / 1m @ Z <sub>N</sub>
Frequency range		40 - 4.000 Hz
Recom. enclosure vol.	70 / 150 l	2,45 / 5,25 ft <sup>3</sup>
Voice coil diameter	76,2 mm	3 in
Bl factor		19,2 N/A
Moving mass		0,091 kg
Voice coil length		16 mm
Air gap height		8 mm
X <sub>damage</sub> (peak to peak)		30 mm

### THIELE-SMALL PARAMETERS<sup>3</sup>

Resonant frequency, f <sub>s</sub>	36 Hz
D.C. Voice coil resistance, R <sub>e</sub>	5,6 $\Omega$
Mechanical Quality Factor, Q <sub>ms</sub>	8,2
Electrical Quality Factor, Q <sub>es</sub>	0,31
Total Quality Factor, Q <sub>ts</sub>	0,30
Equivalent Air Volume to C <sub>ms</sub> , V <sub>as</sub>	236 l
Mechanical Compliance, C <sub>ms</sub>	215 $\mu$ m / N
Mechanical Resistance, R <sub>ms</sub>	2,5 kg / s
Efficiency, $\eta_0$	3,4 %
Effective Surface Area, S <sub>d</sub>	0,088 m <sup>2</sup>
Maximum Displacement, X <sub>max</sub> <sup>4</sup>	6,3 mm
Displacement Volume, V <sub>d</sub>	555 cm <sup>3</sup>
Voice Coil Inductance, L <sub>e</sub>	1 mH


Notes:

<sup>1</sup> The power capacity is determined according to AES2-1984 (r2003) standard.

<sup>2</sup> Program power is defined as power capacity + 3 dB.

<sup>3</sup> T-S parameters are measured after an exercise period using a preconditioning power test. The measurements are carried out with a velocity-current laser transducer and will reflect the long term parameters (once the loudspeaker has been working for a short period of time).

<sup>4</sup> The X<sub>max</sub> is calculated as  $(L_{vc} - H_{ag})/2 + (H_{ag}/3,5)$ , where L<sub>vc</sub> is the voice coil length and H<sub>ag</sub> is the air gap height.



Note: On axis frequency response measured with loudspeaker standing on infinite baffle in anechoic chamber, 1W @ 1m

### MOUNTING INFORMATION

Overall diameter	388 mm	15,3 in
Bolt circle diameter	370 mm	14,6 in
Baffle cutout diameter:		
- Front mount	350 mm	13,8 in
Depth	163 mm	6,4 in
Net weight	6,1 kg	13,4 lb
Shipping weight	7,1 kg	15,6 lb

### DIMENSION DRAWING

