

Ultra compact loudspeaker system for applications requiring good acoustic and power handling characteristcs in a particulary unobtrusive package. The powerful 5" Neodym coaxial driver provides very wide but precise coverage, distortion free up to levels of over 115 dB. Multiple flying points and connection possibilities make the i 5 system a universal sound reinforcement tool suitable for a wide range of near field applications.

# **PRODUCT SPECIFICATIONS**

Speaker Components	5" Nd (1,5" VC) / 0,75" coaxial
Description	Multi Media Sound System
Power AES / Peak	120 W / 360 W
Impedance nominal	16 Ω
SPL 1 W / Peak @ 1 m	93 dB / 115 dB
Usable Range	110 Hz - 19 kHz (-6 dB)
Tuning Frequency excursion minimum	120 Hz
X-Overpoint acoustical	3,0 kHz
Coverage horizontal / vertical	100° - conical
Max. Splay Angle	
Connectors	2 x Neutrik Speakon NL4MP in/out Coding: 1 +/- HiMid, 2 +/- loop thru 1 x Phoenix
Handles	
Rigging / Fittings	3 x M10
Weight	2,5 kg
Size height x width x depth	15,0 x 15,0 x 17,6 cm
Order No.	00160/black 00160/white (RAL 9010)











# DIMENSIONS



150


150







**Controller Setups**:

http://www.seeburg.net/en/downloads











# **MEASUREMENTS**

#### **Frequency Response with Presets**



2D Directivity Plot - radial



#### www.seeburg.com

#### **ACCESSORIES i 5**



# **Flying Bracket**

for i 5, incl. socket screws, 2 x M10 x 20 mm

Order No. 01204 Order No. 01204/w (white)

### **Knurled Screw**

M10 x 20 mm Order No. 73750 Order No. 73750/w (white)



#### Base Plate, Round

M20, K&M, ø 450 mm, height: 21 mm black zinc die-cast, felt strips on the bottom, weight: 6,7 kg

Order No. 01278/round

#### **Speaker Pole, Light**

adjustable, K&M, incl. M20 Adapter Order No. 03004/set



#### **Phoenix Connector** 2 pol Order No. 08257

4 pol Order No. 08256



## **Truss Clamp** incl. M10 Adapter, max. load 15 kg



# Flange

with ball and socket joint, with additional locking screw, M10 x 15, max. load 15 kg Order No. 08125

#### **Steel Safety**

4 mm x 600 mm, black, max. load 10 kg (BGI 810-3), quick connector undetachably

Order No. 01376/4



# **Flight Case**

for 4 pcs. i 5, with mounted flying brackets 01204, standard, 7,0 mm birch multiplex, PVC coated, partition walls, hinged lid, 2 x recessed sprung handles, 1 x butterfly catch, rubber feet, interior lined with felt. Size (H x W x D): 24,0 x 42,0 x 36,0 cm Order No. 16454

# **Flight Case**

for 2 pcs. i 5, with mounted flying brackets 01204, standard, 7,0 mm birch multiplex, PVC coated, partition walls, hinged lid, 1 x recessed sprung handle, 1 x butterfly catch, rubber feet, interior lined with felt. Size (H x W x D): 24,0 x 42,0 x 19,0 cm

Order No. 16453







Order No. 01221



3

i 5

Produktions- und Vertriebs GmbH

Fon: +49 (0)7307 97 00-0 Fax: +49 (0)7307 97 00-29

Auweg 32 D-89250 Senden-Freudenegg

info@seeburg.net www.seeburg.com <u>SEEBURG</u>